



Stainless Steel Characteristics & Properties

Stainless Steel Grades	Chemical Composition Principal Elements %				Mechanical Properties Annealed Condition				Typical Characteristics
	CR	NI	C	Other Elements	Tensile PSI	Yield PSI	Elong. % IN 2"	Hardness Rockwell	
304	18.00-	8.00-11.00	0.08 max	-	85,000 105,000	35,000	55 / 20	B80 Ann	General purpose "300" series grade for
304L	18.00-	8.00-13.00	0.035 max	-	80,000	30,000	55	B75	Low carbon type 304 where greater
304H	18.00-	8.00-11.00	0.04-0.10	-	85,000	35,000	55	B80	Carbon modified for improved high
310	24.00-	19.00-22.00	0.15 max	-	95,000	45,000	45	B85	High resistance to scaling and oxidation
316	16.00-18.00	11.00-14.00	0.08 max	Mo 2.00-3.00	85,000	35,000	50	B80	Better corrosion resistance than type 304 in reducing media. Good hi-temp strength
316L	16.00-18.00	10.00-15.00	0.035 max	Mo 2.00-3.00	75,000	30,000	50	B75	Low carbon type 316 where greater resistance to carbide precipitation is desired
316H	16.00-18.00	11.00-14.00	0.04-0.10	Mo 2.00-3.00	85,000	35,000	50	B80	Carbon modified for improved temperature strength.
317	18.00-20.00	11.00-14.00	0.08 max	Mo 2.00-4.00	90,000	40,000	45	B85	Similar to type 316 but with better corrosion resistance and creep strength.
321	17.00-	9.00-13.00	0.08 max	Ti 5XC-0.60	90,000	35,000	55	B880	Titanium stabilized against carbide
347	17.00-20.00	9.00-13.00	0.08 max	Cb + Ta 10XC-1.00	95,000	40,000	50	B85	Columbian and tantalum stabilized against carbide precipitation.

Physical Properties (Annealed)

Type	Density LBS/CU. INC.	Specific Elect. Resist OHMS CM/CM2	Specific Heat BTU/LB °F	Thermal Conduct BTU/HR SQ FT/ °F (212°)	Mean Coefficient Of Expansions °F		Tension PSI Modulus Of Elasticity	Magnetic Permeability
					32-312	32-1200		
304/304L	0.29	72	0.12	9.4	9.6 X 10 ⁻⁶	10.4 X 10 ⁻⁶	28.0 X 10 ⁶	1.003
310	0.29	78	0.12	8.2	8.8 X 10 ⁻⁶	9.7 X 10 ⁻⁶	29.0 X 10 ⁶	1.003
316/316L	0.29	74	0.12	9.4	8.9 X 10 ⁻⁶	10.3 X 10 ⁻⁶	28.0 X 10 ⁶	1.003
317	0.29	74	0.12	9.4	8.9 X 10 ⁻⁶	10.3 X 10 ⁻⁶	28.0 X 10 ⁶	1.003
321	0.29	72	0.12	9.3	9.3 X 10 ⁻⁶	10.7 X 10 ⁻⁶	28.0 X 10 ⁶	1.003
347	0.29	73	0.12	9.3	9.3 X 10 ⁻⁶	10.6 X 10 ⁻⁶	28.0 X 10 ⁶	1.003
21-6-9	0.29	-	0.12	9.5	9.3 X 10 ⁻⁶	-	28.5 X 10 ⁶	1.002